



Poles	Dimensions (mm)		
	A	B	C
2*10	9.00	12.35	10.55
2*12	11.00	14.35	12.55
2*15	14.00	17.35	15.55
2*20	19.00	22.35	20.55
2*25	24.00	27.35	25.55

- Specifications :
- Voltage rating: 50V AC / DC
 - Current rating: 0.8A AC / DC
 - Withstanding voltage: 250V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance: ≥100MΩ
 - Contact resistance: ≤20mΩ
 - After environmental testing: ≤30mΩ

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP01-1008WVS-2XNP
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ:
TOLERANCES ARE		30~ ϕ ±	±0.30	ANGLE
		10~30	±0.20	
		5~10	±0.15	
		~ 5	±0.10	±2'
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.
	A		NEW	CHECK.
				APPRO.



深圳市联丰电子有限公司
SHENZHEN LINFENGYING ELECTRONIC CO.,LTD