



P. C. B LAYOUT  
TOLERANCE: ±0.05mm

**■ SPECIFICATIONS**

- Voltage rating: 250V AC, DC
- Current rating: 7A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩ min
- Temperature range: -25° C~+85° C
- Contact resistance: 20mΩ max

**■ WAFER**

- Part No. : 5082WR-04P
- Housing Material : Nylon66 UL94V-2
- Pin Material : Brass
- Contact Area Plating: Over Tin 70u" Plating, Over Nickel 30u" Plating.

● The Dimension Marked "▼" Must Be Recorded

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

<b>APPROVALS</b>		<b>DATE</b>	<p><b>深圳市联丰电子有限公司</b> SHENZHEN LINFENG ELECTRONIC CO.,LTD</p>
<b>DRAWN</b>	ZHIWEI.CHEN	2015.07.07	
<b>CHECKED</b>			
<b>APPROVALS</b>			<b>TITLE:</b> 5.08mm 90°
<b>TOLERANCES ARE</b>			<b>PART NO.</b> GP01-5082WR-4P
30~100μm	±0.30	ANGLE	<b>UNIT:</b> mm
10~30	±0.20		<b>SCALE:</b> 1:1
5~10	±0.15	±2°	<b>PROJ:</b>
~5	±0.10		<b>DRAWING NO.</b>
			<b>SHEET</b> 1 OF 1