



PART NO.	Dimensions (mm)	
	A	B
02	3.00	9.65
03	6.00	12.65
04	9.00	15.65
05	12.00	18.65
06	15.00	21.65
07	18.00	24.65
08	21.00	27.65
09	24.00	30.65
10	27.00	33.65
11	30.00	36.65
12	33.00	39.65

P. C. B. LAYOUT 04P-12P

PCB. LAYOUT: 3 CKT

PCB. LAYOUT: 2 CKT

- SPECIFICATIONS
- Voltage rating: 250V AC, DC
 - Current rating: 5A, AC, DC
 - Withstanding Voltage: 1500V AC/minute
 - Insulation resistance: 1000MΩ min
 - Temperature range: -25° C~+85° C
 - Contact resistance: 20mΩ max
- WAFER
- Part No. : 3045WR-1xNP
 - Poles : 02-12P
 - Housing Material: Nylon66 15%GF UL94V-0 Black
 - Pin Material: Brass
 - Contact Area Plating: Tin-Plated
 - The Dimension Marked “▼” Must Be Recorded

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO. GP01-3045WR-NP	
CHECKED			SCALE: 1:1	
APPROVALS			PROJ.	
TOLERANCES ARE		ANGLE	UNIT: mm	SHEET 1 OF 1
30~øH	±0.30	±2°		
10~30	±0.20			
5~10	±0.15			
~ 5	±0.10			
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.
	A		NEW	

深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD