



PART NO.	Dimensions (mm)	
	A	B
02	---	6.65
04	3.00	9.65
06	6.00	12.65
08	9.00	15.65
10	12.00	18.65
12	15.00	21.65
14	18.00	24.65
16	21.00	27.65
18	24.00	30.65
20	27.00	33.65
22	30.00	36.65
24	33.00	39.65

- SPECIFICATIONS**
- Voltage rating: 250V AC, DC
 - Current rating: 5A, AC, DC
 - Withstanding Voltage: 1500V AC/minute
 - Insulation resistance: 1000M Ω min
 - Temperature range: -25 $^{\circ}$ C~+85 $^{\circ}$ C
 - Contact resistance: 20m Ω max
- WAFER**
- Part No. : 3045WR-2xNP
 - Poles : 02-24P
 - Housing Material: Nylon66 15%GF UL94V-0 Black
 - Pin Material: Brass
 - Contact Area Plating: Tin-Plated
 - The Dimension Marked “▼” Must Be Recorded

APPROVALS		DATE		TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07		PART NO. GP01-3045WR-2*NP	
CHECKED				SCALE: 1:1	
APPROVALS				PROJ.	
TOLERANCES ARE				UNIT: mm	DRAWING NO.
30~以上	±0.30	ANGLE	±2'	SHEET 1 OF 1	
10~30	±0.20				
5~10	±0.15				
~ 5	±0.10				

深圳市联丰电子有限公司
SHENZHEN LINFENGYING ELECTRONIC CO.,LTD

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW