



Circuit No.	Dimensions			
	A	B	C	D
02P	2.00	8.00	4.72	6.52
03P	4.00	10.00	6.72	8.52
04P	6.00	12.00	8.72	10.52
05P	8.00	14.00	10.72	12.52
06P	10.00	16.00	12.72	14.52
07P	12.00	18.00	14.72	16.52
08P	14.00	20.00	16.72	18.52
09P	16.00	22.00	18.72	20.52
10P	18.00	24.00	20.72	22.52
11P	20.00	26.00	22.72	24.52
12P	22.00	28.00	24.72	26.52
13P	24.00	30.00	26.72	28.52
14P	26.00	32.00	28.72	30.52
15P	28.00	34.00	30.72	32.52
16P	30.00	36.00	32.72	34.52

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:
DRAWN	ZHIWEI.CHEN	2015.07.07	
CHECKED			
APPROVALS			PART NO. GP01-2001WRS-NP
TOLERANCES ARE			SCALE: 1:1
30~以上	±0.30	ANGLE	PROJ.
10~30	±0.20	UNIT: mm	DRAWING NO.
5~10	±0.15		
~ 5	±0.10	±2'	SHEET 1 OF 1

深圳市联丰电子有限公司
SHENZHEN LIANFENG ELECTRONIC CO.,LTD

SPECIFICATIONS
 Current Rating: 2A AC,DC
 Voltage Rating: 100V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass/Matte Tin-plated or Gold-flash
 Solder Tabs: Brass/Matte Tin-plated or Gold-flash
 Material: Nylon 6T,UL94V-0
 Color: Black