



技术要求

1. 塑件表面应平整、光洁、色泽均匀,无飞边、无纹裂、浇口无拉伤、气泡、变形、缺料等影响使用性能的缺陷
2. 端子表面无氧化、电镀不良等现象
3. 工作温度: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
4. 额定电压: 250V AC DC
5. 额定电流: 2.0A AC DC MAX
6. 接触电阻: $\leq 0.02\Omega$ MAX
7. 绝缘电阻: 1000M Ω MIN
8. 耐压值: 800V AC/minute

孔数	A	B
2	2.0	6.1
3	4.0	8.1
4	6.0	10.1
5	8.0	12.1
6	10.0	14.1
7	12.0	16.1
8	14.0	18.1
9	16.0	20.1
10	18.0	22.1
11	20.0	24.1
12	22.0	26.1
13	24.0	28.1
14	26.0	30.1
15	28.0	32.1
16	30.0	34.1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO. GP01-2001WR-NP-L	
CHECKED			SCALE: 1:1	
APPROVALS			PROJ. SHEET 1 OF 1	
TOLERANCES ARE		ANGLE	DRAWING NO.	
30 ^{以上}	±0.30	±2°		
10~30	±0.20			
5~10	±0.15			
~5	±0.10			



深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD

P.C.B LAYOUT