



- SPECIFICATION**
- 1 Contact resistance: $\leq 20m\Omega$
 - 2 Insulation resistance: $\geq 1000M\Omega$
 - 3 Rated voltage: 125 V AC DC
 - 4 Rated current: 2.0 A AC DC
 - 5 Withstand Voltage: 1000V AC/minute
 - 6 Temperature Range: $-25^{\circ}C \sim +85^{\circ}C$

Circuits	Dimensions (mm)		
	A	B	C
2	2.00	8.00	2.80
3	4.00	10.00	3.20
4	6.00	12.00	3.50
5	8.00	14.00	5.50
6	10.00	16.00	7.50
7	12.00	18.00	9.50
8	14.00	20.00	11.50
9	16.00	22.00	13.50
10	18.00	24.00	15.50
11	20.00	26.00	15.50
12	22.00	28.00	15.50
13	24.00	30.00	15.50
14	26.00	32.00	15.50
15	28.00	34.00	15.50

SUGGESTED PCB LAYOUT
(COMPONENT SIDE)

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	2.00mm Crimp Style Connector	
CHECKED			PART NO. GP01-2002WRS-XP	
APPROVALS			SCALE: 1:1	
TOLERANCES ARE		ANGLE	UNIT: mm	PROJ:
30~以上	±0.30			
10~30	±0.20	±2°	DRAWING NO.	
5~10	±0.15			
~5	±0.10			



深圳市联丰电子有限公司
SHENZHEN LINFENGYING ELECTRONIC CO.,LTD