



Electrical properties

- 1 Current rating:7A AC\DC (AMG #26)
- 2 Voltage rating: 250V AC\DC
- 3 Temperature range: -25°C to 85°C
- 4 Contact resistance:Initial value/30m Ω max
- 5 Insulation resistance:1000M Ω min
- 6 Withstanding voltage:1000V AC/ minute
- 7 Applicable wire:AMG #18 to #22

Environmental controls

- 1 Banned contains SS - 00259 are restricted substance
 - 2 The corresponding issued by SGS or ITS icp-aes data
- Not the material in a list, and validity.

Pin	A	B	C
2	3.96	11.88	8.6
3	7.92	15.84	12.56
4	11.88	19.8	16.52
5	15.84	23.76	20.48
6	19.8	27.72	24.44
7	23.76	31.68	28.4
8	27.72	35.64	32.36
9	31.68	39.6	36.32
10	35.64	43.56	40.28

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW
CHANGE.	CHECK.	APPRO.	

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO. GP01-3961WVS-NP	
CHECKED			SCALE: 1:1	
APPROVALS			PROJ:	
TOLERANCES ARE		ANGLE	UNIT: mm	DRAWING NO.
30~以上	±0.30			
10~30	±0.20	±2°		
5~10	±0.15			
~ 5	±0.10			

深圳市联丰电子有限公司
 SHENZHEN LINFENG ELECTRONIC CO.,LTD