



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass/Gold-flash
 Solder Tabs: Brass/Tin-plated
 Cap: Nylon 6T,UL94V-0,Natural(Beige)
 Wafer: Nylon 6T,UL94V-0
 Color: Natural(Beige)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
1252WVS-2X05P	5.00	12.50
1252WVS-2X07P	7.50	15.00
1252WVS-2X10P	11.25	18.75
1252WVS-2X15P	17.50	25.00
1252WVS-2X20P	23.75	31.25

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE				
DRAWN	ZHIWEI.CHEN	2015.07.07	深圳市联丰电子有限公司			
CHECKED			SHENZHEN LINFENG ELECTRONIC CO.,LTD			
APPROVALS			TITLE:	PART NO.	SCALE:	PROJ. SHEET
TOLERANCES ARE	30~以上 ±0.30	10~30 ±0.20	ANGLE	UNIT: mm	1:1	1 OF 1
	5~10 ±0.15	~5 ±0.10	±2°	DRAWING NO.		