



P. C. B LAYOUT

Technical Data
 Material: Pin(outer sleeve):Brass, machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated:2μm/80μ"Ni, 5μm/200μ"Sn
 Gold Plated:2μm"/80μ"Ni, 0.8μ" gold
 Insulator:PPS UL94V-0

Electrical:
 Current rating:3Amps/contact max.
 Contact resistance:≤4mΩ/contact
 Insulation resistance:≥1000MΩ at V=100V
 Dielectric Withstanding Voltage:1000V AV Min
 Operating voltage:60VAC/DC

Mechanical:
 Operating temperature:-40° C to+105° C
 Soldering temperature:+255° C
 Critical Dimensions:⊗

APPROVALS		DATE	TITLE:	
DRAWN	ZHWEI.CHEN	2015.07.07	PART NO.	GP22-2520WR-NP-1776A
CHECKED			SCALE:	1:1
APPROVALS			PROJ:	
TOLERANCES ARE		30~以上 ±0.30	UNIT:	mm
		10~30 ±0.20	DRAWING NO.	
		5~10 ±0.15		
		~ 5 ±0.10		
ANGLE	±2°			
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.
	A		NEW	CHECK.
				APPRO.