



SPECIFICATIONS

Current Rating: 1amps
 Insulator resistance: 500 Megohms min.
 Dielectric Withstanding: AC 500V
 Operating Temperature: -40°C TO +105°C
 Insulator Material: NY-6T
 Contact Material: Brass
 Plating: Gold flash

UNSPECIFIED TOLERANCE: ±0.20

Dimen Sions List

Contacts Per Row	A	B	Contacts Per Row	A	B
2*02	2.54	1.27	2*22	27.94	26.67
2*03	3.81	2.54	2*23	29.21	27.94
2*04	5.08	3.81	2*24	30.48	29.21
2*05	6.35	5.08	2*25	31.75	30.48
2*06	7.62	6.35	2*26	33.02	31.75
2*07	8.89	7.62	2*27	34.29	33.02
2*08	10.16	8.89	2*28	35.56	34.29
2*09	11.43	10.16	2*29	36.83	35.56
2*10	12.70	11.43	2*30	38.10	36.83
2*11	13.97	12.70	2*31	39.37	38.10
2*12	15.24	13.97	2*32	40.64	39.37
2*13	16.51	15.24	2*33	41.91	40.64
2*14	17.78	16.51	2*34	43.18	41.91
2*15	19.05	17.78	2*35	44.45	43.18
2*16	20.32	19.05	2*36	45.72	44.45
2*17	21.59	20.32	2*37	46.99	45.72
2*18	22.86	21.59	2*38	48.26	46.99
2*19	24.13	22.86	2*39	49.53	48.26
2*20	25.40	24.13	2*40	50.80	49.53
2*21	26.67	25.40			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	
CHECKED			
APPROVALS			PART NO.	1270WR-2XNP
TOLERANCES ARE		ANGLE	UNIT: mm	SCALE: 1:1
30°以上	±0.30			PROJ.
10~30	±0.20			SHEET 1 OF 1
5~10	±0.15			
~ 5	±0.10	±2°	DRAWING NO.	
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.
	A		NEW	CHECK.
				APPRO.

深圳市联丰电子有限公司
 SHENZHEN LIANFENG ELECTRONIC CO.,LTD