



Technical Data

Material:

Pin(outer sleeve): Brass, machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated: 2μm/80μ"Ni, 5μm/200μ"Sn

Gold Plated: 2μm"/80μ"Ni, 0.8μ" gold

Insulator: PPS UL94V-0

Mating pin∅: 0.43mm

Electrical:

Current rating: 1Amps/contact max.

Contact resistance: ≤ 4mΩ/contact

Insulation resistance: ≥ 1000MΩ at V=100V

Operating voltage: 60VAC/DC

Mechanical:

Mechanical life: min 500 cycle

Operating temperature: -40 ° C to +105 ° C

Soldering temperature: +255 ° C

Critical Dimensions: (*)

P. C. B LAYOUT

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP22-1273WV-NP-0800A
CHECKED			SCALE:	1:1
APPROVALS			PROJ:	
TOLERANCES ARE		ANGLE	UNIT:	mm
30~以上	±0.30	±2°	DRAWING NO.	
10~30	±0.20			
5~10	±0.15			
~ 5	±0.10			



深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD