



SPECIFICATIONS

Current Rating: 2A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Gold-flash
 Material: Nylon 9T,UL94V-0
 Color: Natural(Black)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
2X05P	8.00	17.10
2X06P	10.00	19.10
2X07P	12.00	21.10
2X08P	14.00	23.10
2X10P	18.00	27.10
2X11P	20.00	29.10
2X12P	22.00	31.10
2X13P	24.00	33.10
2X15P	28.00	37.10
2X17P	32.00	41.10
2X20P	38.00	47.10
2X22P	42.00	51.10
2X24P	46.00	55.10
2X25P	48.00	57.10
2X30P	58.00	67.10
2X32P	62.00	71.10

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:
DRAWN	ZHIWEI.CHEN	2015.07.07	2.00mm Crimp Style Connector
CHECKED			PART NO. GP23-2023WR-2XNP
APPROVALS			SCALE: 1:1
TOLERANCES ARE		30~以上 ±0.30	ANGLE
		10~30 ±0.20	UNIT: mm
		5~10 ±0.15	DRAWING NO.
		~ 5 ±0.10	SHEET 1 OF 1



深圳市联丰电子有限公司
 SHENZHEN LINFENG ELECTRONIC CO.,LTD