



**SPECIFICATIONS**

Contact Resistance: 3 aperes Max  
 Current Rationg: 3m Max  
 Insulator Resistance: 1000 Megohms Max  
 Dielectric Withstanding Voltage:  
 AC 650 Volts RMS at sealeve

**Dimensions list**

Contacts Per row	Dimensions	
	A	B
1	2.0 (0.079)	0 (0)
2	4.0 (0.157)	2.0 (0.079)
3	6.0 (0.236)	4.0 (0.157)
4	8.0 (0.315)	6.0 (0.236)
5	10.0 (0.393)	8.0 (0.315)
6	12.0 (0.472)	10.0 (0.393)
7	14.0 (0.551)	12.0 (0.472)
8	16.0 (0.630)	14.0 (0.551)
9	18.0 (0.709)	16.0 (0.630)
10	20.0 (0.787)	18.0 (0.709)

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

<b>APPROVALS</b>		<b>DATE</b>	<p><b>深圳市联丰电子有限公司</b> SHENZHEN LINFENG ELECTRONIC CO.,LTD</p>							
<b>DRAWN</b>	ZHIWEI.CHEN	2015.07.07								
<b>CHECKED</b>			<b>TITLE:</b>	MINI JUMPER PITCH2.0mm						
<b>APPROVALS</b>			<b>PART NO.</b>	GP25-2022WV-NP-M						
<b>TOLERANCES ARE</b>	30~ <sup>±</sup> 0.30 10~ <sup>±</sup> 0.20 5~ <sup>±</sup> 0.15 ~ 5	±0.30 ±0.20 ±0.15 ±0.10	<b>ANGLE</b>	±2°	<b>UNIT:</b> mm	<b>SCALE:</b> 1:1	<b>PROJ:</b>	<b>DRAWING NO.</b>		<b>SHEET</b> 1 OF 1