



NOTE:  
 1.MATERIAL:  
 a.HOUSING:PA66  
 b.CONTACT:PHOSPHOR BRONZE  
 (SURFACE PLATING: Sn 100u"-120u")  
 2.ELECTRIC:  
 a.CONTACT RESISTANCE: 30 MILLIOHMS MAX  
 b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN  
 c.DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL  
 d.OPERATING TEMPERATURE: -25°C~ +85°C

PCB Layout Diagram  
 Top View

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP07-CR2032-20
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ:
TOLERANCES ARE		30~Ø1.1 ±0.30	ANGLE	±2°
		10~30 ±0.20		
		5~10 ±0.15		
		~ 5 ±0.10		
SHENZHEN LINRENYING ELECTRONIC CO.,LTD		SHEET 1 OF 1		

