



PCB Layout Diagram
Top View

NOTE:

1. MATERIAL:

- a. HOUSING: PBT BLACK
- b. CONTACT: Mn Steel, BRASS

(SURFACE PLATING: SN100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25 ° C ~ +85 ° C

3	TERMINAL (-)	1	BRASS, T=0.85MM	Sn-Plating
2	TERMINAL (+)	1	Mn Steel, T=0.40MM	Sn-Plating
1	HOUSING	1	PBT	BLACK
NO	PART NAME	QTY	MATERIAL	PLATING & COLOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	电池座	
CHECKED			PART NO.	GP07-CR1620-01
APPROVALS			UNIT: mm	SCALE: 1:1
TOLERANCES ARE		30~以上 ±0.30	ANGLE	±2°
		10~30 ±0.20	DRAWING NO.	
		5~10 ±0.15		
		~ 5 ±0.10		


深圳市联丰电子有限公司
 SHENZHEN LINFENG ELECTRONIC CO.,LTD